

18 Gauge Narrow Crown Stapler



WS4840

Applications

Cabinet Assembly, Door & Window Manufacturing,
Drawer Assembly, Floor Underlayment, Furniture
Assembly, Underlayment

Specifications

Staple Crown	1/4"
Staple Gauge	18 Ga
Staple Length	1/2" to 1-5/8"
Staple Capacity	168
Firing Mode	Restrictive
Dimensions	12" x 2-1/2" x 9-1/2"
Weight	3.9 lbs
Air Pressure	80-100 p.s.i.

Features

360° Adjustable Exhaust, Adjustable
Depth Control, Bump Fire Trigger
Included, Long Magazine Available,
Quick Clear Nose, Rubber Grip For
Comfort

Includes

Plastic Carrying Case, Safety Glasses,
Tool Oil, Manual, Parts Diagram



For best results, use Spotnails® collated fasteners

PG - Made of High Tensile Wire

Stock No.	Length	Desc.	M/Bx	Bx/ Cs	M/ Cs	Lbs/ Cs	Cs/ Skid
4804PG-50M	1/2"	Galv.	5.00	10	50.0	26.40	60
4805PG-50M	5/8"	Galv.	5.00	10	50.0	33.90	64
4806PG-50M	3/4"	Galv.	5.00	10	50.0	38.40	48
4807PG-50M	7/8"	Galv.	5.00	10	50.0	43.40	48
4808PG-50M	1"	Galv.	5.00	10	50.0	51.10	48
4809PG-30M	1-1/8"	Galv.	5.00	6	30.0	35.40	64
4810PG-30M	1-1/4"	Galv.	5.00	6	30.0	38.50	48
4811PG-30M	1-3/8"	Galv.	5.00	6	30.0	41.30	48
4812PG-30M	1-1/2"	Galv.	5.00	6	30.0	46.10	48
4813PG-30M	1-5/8"	Galv.	5.00	6	30.0	51.00	48

4805CG-50M	5/8"	Cross,Chisel, Galv.	5.00	10	50.0	50.60	60
4806CG-50M	3/4"	Cross,Chisel, Galv.	5.00	10	50.0	37.40	48

4807DG-50M	7/8"	Divergent, Galv	5.00	10	50.0	45.10	48
4809DG-30M	1-1/8"	Divergent, Galv	5.00	6	30.0	33.30	60

4805OCG-50M	5/8"	Outward Clinch	5.00	10	50.0	32.30	60
-------------	------	----------------	------	----	------	-------	----

4811PN-30M	1-3/8"	Nylon	5.00	6	30.0	41.00	48
------------	--------	-------	------	---	------	-------	----

304 Stainless Steel

4803PS-50M	3/8"	304 SS	5.00	10	50.0	21.90	60
4805PS-25M	5/8"	304 SS	2.50	10	25.0	17.80	60
4806PS-25M	3/4"	304 SS	2.50	10	25.0	19.90	48
4807PS-25M	7/8"	304 SS	2.50	10	25.0	22.70	48
4808PS-25M	1"	304 SS	2.50	10	25.0	25.50	48
4810PS-25M	1-1/4"	304 SS	2.50	10	25.0	32.50	48
4812PS-25M	1-1/2"	304 SS	2.50	10	25.0	38.30	48

Division of Peace Industries, LTD.

Phone: 800-873-2239 ** Fax: 888-369-2588

www.spotnails.com

